



| SCIGRIP® NUMBER  | PRODUCT DESCRIPTION  | SIZE             | UNITS/ CASE | APPROX. LBS / CASE | CONTAINER CODE* | STOCK NUMBER | MSRP (UNIT) |
|--|--|------------------|-------------|--------------------|-----------------|--------------|-------------|
| <b>3</b>   | <b>Non-Flammable</b> <span style="float:right"><b>CLEAR</b></span><br>Water-thin, very fast set solvent cement for acrylics. Will also bond styrene, butyrate and polycarbonate to themselves.<br><b>Working Time:</b> 1 minute <b>Fixture Time:</b> 2 minutes <b>Shelf Life:</b> 2 years<br><i>Where not for sale in California (SCAQMD), please use SCIGRIP #4SC.</i>  | Gallon           | 4           | 51                 | MC,SC           | 10299        | 73.94       |
|  |  | Quart            | 4           | 14                 | MC,SC           | 12754        | 18.87       |
|  |  | Pint             | 6           | 10                 | MC,SC           | 10300        | 12.00       |
|  |  | 1/4 Pint         | 24          | 11                 | MC,SC           | 10799        | 6.15        |
| <b>4</b>   | <b>Non-Flammable</b> <span style="float:right"><b>CLEAR</b></span><br>Water-thin, moderately fast set solvent cement for acrylics. Will also bond styrene, butyrate and polycarbonate to themselves.<br><b>Working Time:</b> 1-2 minutes <b>Fixture Time:</b> 3 minutes <b>Shelf Life:</b> 2 years<br><i>Where not for sale in California (SCAQMD), please use SCIGRIP #4SC.</i>   | Gallon           | 4           | 51                 | MC,SC           | 10306        | 73.94       |
|  |  | Quart            | 4           | 14                 | MC,SC           | 12755        | 18.87       |
|  |  | Pint             | 6           | 10                 | MC,SC           | 10307        | 12.00       |
|  |  | 1/4 Pint         | 24          | 11                 | MC,SC           | 10308        | 6.15        |
| <b>4SC</b><br><b>NEW!</b><br>                          | <b>Non-Flammable</b> <span style="float:right"><b>CLEAR</b></span><br>Water-thin, fast set solvent cement for acrylics. Will also bond styrene, butyrate and polycarbonate to themselves.<br><b>Working Time:</b> 1-2 minutes <b>Fixture Time:</b> 3 minutes <b>Shelf Life:</b> 2 years  | Gallon           | 4           | 51                 | MC,SC           | 13415        | 75.68       |
|  |  | Pint             | 6           | 10                 | MC,SC           | 13417        | 12.57       |
|  |  | 1/4 Pint         | 24          | 11                 | MC,SC           | 13418        | 6.13        |
| <b>16</b><br>  | <b>Non-Flammable</b> <span style="float:right"><b>CLEAR</b></span><br>Fast drying, high strength, medium bodied cement for acrylics. Will also bond styrene, butyrate, polycarbonate, other plastics and porous surfaces.<br><b>Working Time:</b> 5-6 minutes <b>Fixture Time:</b> 10 minutes <b>Shelf Life:</b> 2 years   | Gallon           | 4           | 41                 | MC,SC           | 10313        | 83.63       |
|  |  | Pint             | 6           | 8                  | MC,SC           | 10314        | 14.35       |
|  |  | 5 oz. Tube       | 24          | 9                  | MT              | 10315        | 6.09        |
|  |  | 1.5 oz. Tube     | 48          | 6                  | MT              | 10319        | 3.71        |
| <b>28</b><br><b>KIT</b><br>                            | <b>Non-Flammable</b> <span style="float:right"><b>CLEAR</b></span><br>Hand mixed three-component, reactive, high strength acrylic based adhesive with excellent weatherability. Mil Spec A-8576C Type II.<br><b>Working Time:</b> 15 minutes <b>Fixture Time:</b> 2 hours <b>Shelf Life:</b> 1 year  | Pint             | 12          | 19                 | PC,SC           | 11780        | 41.39       |
|  |  |                  |             |                    |                 |              |             |
| <b>40</b><br><b>KIT</b><br>                            | <b>Non-Flammable</b> <span style="float:right"><b>CLEAR</b></span><br>Hand mixed two-component 20:1, reactive, high strength acrylic based adhesive provides "museum quality" water clear joints with excellent weatherability. Mil Spec A-8576C Type III. Optional, use #3061 thinner for #40 (A).<br><b>Refrigeration Recommended.</b><br><b>Working Time:</b> 20 minutes <b>Fixture Time:</b> 2 hours <b>Shelf Life:</b> 1 year | Gallon           | 4           | 38                 | PC,SC           | 11265        | 126.13      |
|  |  | Pint             | 12          | 19                 | PC,SC           | 11266        | 26.01       |
| <b>42</b><br><b>50 ml Cartridge</b><br><b>NEW!</b><br> | <b>Non-Flammable</b> <span style="float:right"><b>CLEAR</b></span><br>Two-component 10:1, reactive, high strength acrylic based adhesive provides "museum quality" water clear joints with excellent weatherability. Mil Spec A-8576C Type III.<br><b>Refrigeration Recommended.</b><br><b>Working Time:</b> 15 minutes <b>Fixture Time:</b> 2 hours <b>Shelf Life:</b> 1 year   | 50 ml Cartridge  | 12          | 3                  | Cartridge       | 13578        | 24.91       |
|  |  | Mixing Tip       | 12          | 1                  | Each            | 13586        | 1.25        |
|  |  | 50 ml 10:1 Gun   | 1           | 1                  | Box             | 13584        | 76.27       |
| <b>42</b><br><b>230 ml Cartridge</b><br>               | <b>Non-Flammable</b> <span style="float:right"><b>CLEAR</b></span><br>Two-component 10:1, reactive, high strength acrylic based adhesive provides "museum quality" water clear joints with excellent weatherability. Mil Spec A-8576C Type III.<br><b>Refrigeration Recommended.</b><br><b>Working Time:</b> 15 minutes <b>Fixture Time:</b> 2 hours <b>Shelf Life:</b> 1 year   | 230 ml Cartridge | 12          | 11                 | Cartridge       | 10987        | 54.05       |
|  |  | Mixing Tip       | 12          | <1                 | Package         | 13147        | 2.58        |
|  |  | 230 ml Gun       | 1           | 12                 | Box             | 11778        | 277.77      |
| <b>1802</b>  | <b>Non-Flammable</b> <span style="float:right"><b>CLEAR</b></span><br>Thin bodied, moderately fast set. For bonding acrylics, styrene, PVC, ABS and butyrate to themselves or each other.<br><b>Working Time:</b> 8 minutes <b>Fixture Time:</b> 10-15 minutes <b>Shelf Life:</b> 3 years  | Gallon           | 4           | 34                 | MC,SC           | 10350        | 80.65       |
|  |  | Pint             | 6           | 7                  | MC,SC           | 10351        | 16.51       |
| <b>3061</b><br>VOC Free                                | <b>Non-Flammable</b> <span style="float:right"><b>CLEAR</b></span><br>Thinner for #40 (A) (Acrylic Monomer).<br><b>Working Time:</b> N/A <b>Fixture Time:</b> N/A <b>Shelf Life:</b> 2 years   | Pint             | 6           | 14                 | MC,SC           | 11283        | 15.95       |

ACRYLIC SUBSTRATES





\* These products meet requirements of California South Coast Air Quality Management District (SCAQMD) Rule 1168.

See back page for more information.

|  | SCIGRIP® NUMBER   | PRODUCT DESCRIPTION  | SIZE  | UNITS/CASE | APPROX. LBS./CASE | CONTAINER CODE* | STOCK NUMBER | MSRP (UNIT) |       |
|--|---|--|---|------------|-------------------|-----------------|--------------|-------------|-------|
| POLYCARBONATE SUBSTRATES   | <b>55</b><br>VOC Free   | Two-component 1:1, reactive urethane based adhesive for bonding polycarbonate, butyrate, ABS and PETG. Excellent UV light resistance. Does not alter the impact resistance of polycarbonate.<br><b>Working Time:</b> 5-6 minutes <b>Fixture Time:</b> 1-2 hours <b>Shelf Life:</b> 1 year  | CLEAR<br>50 ml Cartridge<br>Mixing Tip<br>(New) 43 ml / 50 ml Gun (1:1 / 4:1)<br>Replaces 11193 | 12         | 3                 | Cartridge       | 11272        | 24.08       |       |
|  |   |  |   | 12         | <1                | Each            | 11195        | 1.17        |       |
|  |   |  |   | 1          | <1                | Box             | 13585        | 73.36       |       |
| POLYCARBONATE SUBSTRATES   | <b>58</b><br>VOC Free   | Two-component 1:1, reactive urethane based adhesive for bonding polycarbonate, butyrate, ABS and PETG. Excellent UV light resistance. Does not alter the impact resistance of polycarbonate.<br><b>Working Time:</b> 2-3 minutes <b>Fixture Time:</b> 20 minutes <b>Shelf Life:</b> 1 year | CLEAR<br>50 ml Cartridge<br>Mixing Tip<br>(New) 43 ml / 50 ml Gun (1:1/4:1)<br>Replaces 11193   | 12         | 3                 | Cartridge       | 12373        | 24.08       |       |
|  |   |  |   | 12         | <1                | Each            | 11195        | 1.17        |       |
|  |   |  |   | 1          | <1                | Box             | 13585        | 73.36       |       |
| VINYL, PVC, CPVC SUBSTRATES  | <b>66</b><br>  | Thin syrup, fast curing, high strength. Instant contact strength. For flexible vinyl, urethane, wood, canvas, etc. Long working time.<br><b>Working Time:</b> 2-20 minutes <b>Fixture Time:</b> 45-60 minutes <b>Shelf Life:</b> 3 years   | CLEAR   | Gallon     | 4                 | 33              | MC,SC        | 10461       | 72.23 |
|  |   |  |   | Pint       | 6                 | 7               | MC,AC        | 10462       | 14.18 |
|  | <b>1001</b>   | Thin syrup, slow set, rigid bond. For rigid or flexible vinyl to aluminum, glass, wood, etc.<br><b>Working Time:</b> 15-20 minutes <b>Fixture Time:</b> 30 minutes <b>Shelf Life:</b> 3 years  | CLEAR   | Gallon     | 4                 | 36              | MC,SC        | 10419       | 82.22 |
|  |   |  |   |            |                   |                 |              |             |       |
|  | <b>1829</b>   | For many plastics and non-plastic materials, e.g., vinyls, acrylics, urethane, foam, polyester, wood, metal, etc.<br><b>Working Time:</b> 2-5 minutes <b>Fixture Time:</b> 2-4 hours <b>Shelf Life:</b> 2 years  | TAN   | Gallon     | 4                 | 35              | MC,SC        | 10552       | 72.93 |
|  |   |  |   | 1/4 Pint   | 24                | 8               | MC,AC        | 10554       | 5.95  |
|  | <b>1909</b>   | Medium syrup, fast set, flexible bond. For flexible vinyl, ABS, canvas, fabrics, acrylics, butyrate and polyurethane. Water resistant.<br><b>Working Time:</b> 10-15 minutes <b>Fixture Time:</b> 20-25 minutes <b>Shelf Life:</b> 3 years   | CLEAR   | Gallon     | 4                 | 35              | MC,SC        | 10431       | 97.82 |
|  |   |  |   |            |                   |                 |              |             |       |
|  | <b>1910</b>   | Heavy syrup, slow set, solvent cement. For foamed, rigid and flexible PVC to themselves. Not for joining dissimilar materials.<br><b>Working Time:</b> 15 minutes <b>Fixture Time:</b> 20-25 minutes <b>Shelf Life:</b> 3 years  | CLEAR   | Gallon     | 4                 | 35              | MC,SC        | 10437       | 97.82 |
|  |   |  |   |            |                   |                 |              |             |       |
| <b>2007</b>  | Water-thin, very fast set solvent cement. For foamed, rigid and flexible PVC to themselves and each other. Not for joining dissimilar materials.<br><b>Working Time:</b> 1-2 minutes <b>Fixture Time:</b> 3 minutes <b>Shelf Life:</b> 3 years                            | CLEAR  | Gallon  | 4          | 33                | MC,SC           | 10447        | 77.16       |       |
|  |   |  | Pint  | 6          | 7                 | MC,SC           | 10448        | 14.20       |       |
| <b>4007</b><br> | Medium bodied syrup, very fast set, rigid bond. For rigid vinyl.<br><b>Working Time:</b> 20 minutes <b>Fixture Time:</b> 25 minutes <b>Shelf Life:</b> 3 years  | CLEAR  | Gallon  | 4          | 37                | MC,SC           | 11125        | 85.80       |       |
|  |   |  |   |            |                   |                 |              |             |       |
| <b>4052</b><br> | Medium syrup, fast set solvent cement. Multi-purpose for PVC, CPVC, ABS, styrene, nylon, foamed PVC, etc.<br><b>Working Time:</b> 15 minutes <b>Fixture Time:</b> 20-25 minutes <b>Shelf Life:</b> 2 years  | CLEAR  | Gallon  | 4          | 36                | MC,SC           | 11137        | 89.25       |       |
|  |   |  | Pint  | 6          | 8                 | MC,SC           | 11138        | 17.71       |       |
| <b>4784</b><br> | Medium syrup, fast set, flexible bond. For flexible or rigid vinyl to itself or other materials such as fabrics, acrylics, butyrate and polyurethane. Weather resistant.<br><b>Working Time:</b> 20 minutes <b>Fixture Time:</b> 20-30 minutes <b>Shelf Life:</b> 3 years | CLEAR  | Gallon  | 4          | 36                | MC,SC           | 13177        | 128.99      |       |
|  |   |  | Pint  | 6          | 8                 | MC,SC           | 13178        | 20.33       |       |
|  |   |  | 1.5 oz. Tube  | 24         | 3                 | MT              | 13179        | 4.24        |       |
| ABS SUBSTRATES   | <b>1707</b>   | Medium syrup, fast set. Dries milky translucent. For cementing ABS ONLY!<br><b>Working Time:</b> 10 minutes <b>Fixture Time:</b> 15-20 minutes <b>Shelf Life:</b> 3 years  | MILKY   | Gallon     | 4                 | 34              | MC,SC        | 10484       | 62.51 |
|  |   |  |   | Pint       | 6                 | 7               | MC,SC        | 10486       | 13.89 |
|  | <b>2354</b>   | Water-thin, fast set solvent cement. For bonding ABS and styrene to themselves. Not for joining dissimilar materials.<br><b>Working Time:</b> 3 minutes <b>Fixture Time:</b> 5 minutes <b>Shelf Life:</b> 3 years  | CLEAR   | Gallon     | 4                 | 31              | MC,SC        | 10490       | 52.23 |
| Pint   |   |  |   | 6          | 7                 | MC,SC           | 10491        | 12.52       |       |
| <b>4707</b><br> | Heavy syrup, fast set, dries milky translucent. For cementing ABS ONLY! (Low VOC version of 1707®.)<br><b>Working Time:</b> 10 minutes <b>Fixture Time:</b> 10-15 minutes <b>Shelf Life:</b> 3 years  | MILKY  | Gallon  | 4          | 34                | MC,SC           | 11128        | 62.51       |       |
|  |   |  | Pint  | 6          | 7                 | MC,SC           | 11129        | 13.60       |       |
| STYRENE  | <b>4807</b><br>  | Medium syrup, fast set. For bonding styrene to itself.<br><b>Working Time:</b> 10-15 minutes <b>Fixture Time:</b> 20 minutes <b>Shelf Life:</b> 3 years  | MILKY   | Gallon     | 4                 | 34              | MC,SC        | 11131       | 70.81 |

\* These products meet requirements of California South Coast Air Quality Management District (SCAQMD) Rule 1168.

See back page for more information.

|   | SCIGRIP® NUMBER  | PRODUCT DESCRIPTION  | SIZE                      | UNITS/ CASE | APPROX. LBS / CASE | CONTAINER CODE* | STOCK NUMBER     | MSRP (UNIT) |
|---|--|--|---------------------------|-------------|--------------------|-----------------|------------------|-------------|
| STRUCTURAL ADHESIVES  | 10 Kit<br>  | Two-component, high strength structural adhesive. High viscosity. Bonds PVC, acrylics, styrene, ABS, polycarbonates to steel, aluminum, etc. Same physical properties as #11.<br><b>Working Time:</b> 25 minutes <b>Fixture Time:</b> 1 hour <b>Shelf Life:</b> 1 year                       | WHITE<br>Gallon           | 4           | 40                 | PC,SC           | 10179            | 144.61      |
|   |  |  | Pint                      | 4           | 7                  | PC,SC           | 10181            | 28.93       |
|   |  |  | 1/4 Pint                  | 6           | 3                  | PC,SC           | 10182            | 14.23       |
|   | 11 470 ml Cartridge<br>   | Two-component, high strength, acrylic based adhesive packaged in a two-component cartridge for use with a mixing tip and dispensing gun. Same physical properties as #10. <b>(Replaces #811.)</b><br><b>Working Time:</b> 25 minutes <b>Fixture Time:</b> 1 hour <b>Shelf Life:</b> 1.5 year | WHITE<br>470 ml Cartridge | 4           | 8                  | Cartridge       | 13901            | 68.04       |
| Mixing Tip  |  |  | 12                        | <1          | Each               | 13147           | 2.58             |             |
| Low-Resistance Manual Gun   |  |  | 1                         | 4           | Box                | 11652           | 329.12           |             |
| 45<br> | Two-component, 4:1 high strength, methacrylate structural adhesive. High viscosity. Bonds unprepared and corrosion resistant metals, composites and plastics.<br><br><b>Working Time:</b> 5-6 minutes <b>Fixture Time:</b> 15 minutes <b>Shelf Life:</b> 1 year | TAN<br>43 ml Cartridge   | 12                        | 3           | Cartridge          | 12468           | 13.59            |             |
|   |  | 43 ml Mixing Tip   | 12                        | <1          | Each               | 11195           | 1.17             |             |
|   |  | (New) 43 ml / 50 ml Gun (1:1/4:1)<br>Replaces 11193  | 1                         | <1          | Box                | 13585           | 73.36            |             |
|   |  | 400 ml Cartridge   | 4                         | 7           | Cartridge          | 12611           | 44.12            |             |
|   |  | <b>(NEW)</b> 400 ml Mixing Tip   | 10                        | <1          | Each               | 14043           | 2.51             |             |
|   |  | Low-Resistance Manual Gun<br>(New) Manual Gun  | 1<br>1                    | 4<br>4      | Box<br>Box         | 12613<br>13302  | 369.02<br>133.82 |             |
| PPX5 50 ml Cartridge<br>VOC Free  | <b>NEW Plastic Bonder</b> <b>OFF WHITE</b><br>Two-component 10:1, high strength, acrylic based adhesive formulated for bonding low surface energy plastics. Packaged in a two-component cartridge for use with a mixing tip and dispensing gun.<br><b>Working Time:</b> 2-4 minutes <b>Fixture Time:</b> 90 minutes <b>Shelf Life:</b> 6 months  | 50 ml Cartridge  | 12                        | 2           | Cartridge          | 30691           | 49.17            |             |
|   |  | Mixing Tip   | 100                       | 5           | Each               | 150341          | 1.25             |             |
|   |  | Manual Gun   | 1                         | 1           | Box                | 13584           | 76.27            |             |
| CLEANER   | 57 Cleaner   | <b>TRANSPARENT BLUE</b><br>Non-abrasive cleaner for acrylic and most other plastics.<br><b>Working Time:</b> N/A <b>Fixture Time:</b> N/A <b>Shelf Life:</b> 3 years   | Gallon                    | 4           | 32                 | MC,SC           | 11273            | 45.06       |
| APPLICATORS AND ACCESSORIES   | 50 ml 1:1 / 4:1 APPLICATOR GUN<br>NEW!   | Includes a 1:1 and 4:1 plunger. Used with #45, 43 ml cartridges, and #55/#58, 50 ml cartridges. (Supersedes guns #12471 and #11193.) Now one gun with two plungers!  | (New) Manual Gun          | 1           | 1                  | Box             | 13585            | 73.36       |
|   | 50 ml 10:1 MANUAL APPLICATOR GUN   | Includes a 10:1 plunger. Use with #42 and PPX5 cartridges.   | (New) Manual Gun          | 1           | 1                  | Box             | 13584            | 76.27       |
|   | 230 ml 10:1 APPLICATOR GUN   | Use with #42, 230 ml cartridges.   | Low-Resistance Manual Gun | 1           | 1                  | Box             | 11778            | 277.77      |
|   | 400 ml 4:1 APPLICATOR GUN  | Use with #45, 400 ml cartridges.   | Low-Resistance Manual Gun | 1           | 4                  | Box             | 12613            | 369.02      |
|   |  |  | (New) Manual Gun          | 1           | 4                  | Box             | 13302            | 133.82      |
|   | 470 ml/490 ml 10:1 APPLICATOR GUN  | Use with #11, 470 ml cartridges.   | Low-Resistance Manual Gun | 1           | 4                  | Box             | 11652            | 329.12      |
|   |  |  | Pneumatic Gun             | 1           | 8                  | Box             | 11199            | 692.54      |
|   | MIXING NOZZLES   | 50 ml 1:1 & 4:1<br>50 ml 10:1 (New)<br>50 ml 10:1 (New). Use with PPX5 cartridges.<br>400 ml 4:1 (New)<br>470 ml & 490 ml 10:1   |                           | 12          | <1                 | Each            | 11195            | 1.17        |
|   |  |  |                           | 12          | <1                 | Each            | 13586            | 1.25        |
|   |  |  |                           | 100         | 5                  | Each            | 150341           | 1.25        |
|   |  |  | 10                        | <1          | Each               | 14043           | 2.51             |             |
|   |  |  | 10                        | <1          | Each               | 13147           | 2.58             |             |
| Oval 1 1/4 oz DISPENSING BOTTLES  | 14 Gauge 1.5" needle<br>23 Gauge 2" needle<br>25 Gauge 2" needle   |  | 25                        | <1          | Box                | 11713           | 4.11             |             |
|   |  |  | 25                        | <1          | Box                | 11714           | 4.11             |             |
|   |  |  | 25                        | <1          | Box                | 11715           | 4.11             |             |
| MICRO TIP   | For use on 5 oz. and 1.5 oz. #16 and #4784 tubes   |  | 24                        | <1          | Each               | 11718           | 0.77             |             |

• These products meet requirements of California South Coast Air Quality Management District (SCAQMD) Rule 1168.

See back page for more information.

\*Container codes: MC-Metal Can, GC-Glass Container, SC-Screw Cap, MT-Metal Tube, PC-Plastic Container, AC-Applicator Cap.

**Working Time:** Time available to make the bond.

**Fixture Time:** Time required before fixturing or clamping can be removed and gentle handling of the part may occur. See Technical Data Sheets for more information and cure times.

**Shelf Life:** Begins on the date of manufacture. Expired shelf life does not necessarily mean the material has gone bad, but it is beyond IPS's warranty guidelines. Use expired materials at own risk.

**TEST:** It is the customer's responsibility to always test products before proceeding to assure compatibility and bond strength.

## TERM AND CONDITIONS

### PRODUCTS ARE SOLD IN CASE LOTS ONLY.

**DROP SHIP FEE:** ALL DROP SHIP ORDERS LESS THAN \$1250.00 WILL INCUR A \$100.00 DROP SHIP FEE. PRODUCTS ARE SOLD IN CASE LOTS ONLY.

**TERMS OF SALE:** Net 30 days.

**MINIMUM ORDER:** \$100.00 Net.

**FREIGHT TERMS:** IPS Corp. will pay freight to one destination within the United States on SCIGRIP orders meeting a minimum of 500 lbs or \$1,250.00 net. Shipper reserves the right to choose the method of shipment and choice of routing.

**RETURNED GOODS:** IPS Corp. will not accept returned merchandise without prior authorization for RGA Number, which must be displayed on the outside of the shipping carton and packing slip. Authorized returns must be in full case quantities, shipped prepaid and are subject to a 25% Restocking Fee. IPS Corp. will not accept merchandise that has been discontinued or merchandise with less than half of the shelf life remaining.

**WARRANTY:** IPS Corporation ("IPS Corp.") warrants that all new IPS Corp. products shall be of good quality and free from defects in material and workmanship for the shelf life as indicated on the product. If any IPS Corp. product becomes defective, or fails to conform to our written limited warranty under normal use and storage conditions, then IPS Corp. will, without charge, replace the nonconforming product. However, this limited warranty shall not extend to, nor shall IPS Corp. be responsible for, damages or loss resulting from accident, misuse, negligent use, improper application, or incorporation of IPS Corp. products into other products. In addition, any repackaging of IPS Corp. products also shall void the limited warranty. IPS Corp. shall not be responsible for, nor does this limited warranty extend to, consequential damage, or incidental damage or expense, including without limitation, injury to persons or property or loss of use. Please refer to our standard IPS Corp. Limited Warranty for additional provisions.

Each SCIGRIP cement is developed for a specific purpose by skilled technicians in our well equipped laboratory. Every production batch of SCIGRIP cements is checked to assure that consistent quality is maintained. All retained batch samples are kept for a period of at least one year. A batch identification code is stamped on each can which gives the date of manufacture to facilitate your stock rotation. To assist you in the proper selection of SCIGRIP products, a Product Selection Guide is available. For proper selection of SCIGRIP products, it's important to know the specific materials being bonded. We will be pleased to send "no charge" samples for your evaluation.

SCIGRIP products are intended for use by skilled individuals. We urge users to verify by tests that these products, as well as the recommended methods, are suitable for the materials being used in their application. Technical Data Sheets and Material Safety Data Sheets should be read before using our products.

**READ ALL PRODUCT TECHNICAL DATA SHEETS AND MATERIAL SAFETY DATA SHEETS BEFORE USING ANY OF THE LISTED PRODUCTS.**

The information on this Price List is a brief description only. The Buyer/User should contact IPS Corporation or a local distributor to get full detailed technical data and safety information.

**ALWAYS TEST PRODUCTS ON SUBSTRATE TO ASSURE COMPATIBILITY AND BOND STRENGTH**

©2014 SCIGRIP, AA Price List 04/14

### TENNESSEE **WELD-ON**

#### Customer Service / Technical Service

500 Distribution Parkway  
Collierville, TN 38017

Tel: (901) 853-5001

#### Customer Service:

(800) 888-8312

Fax: (901) 853-5008

#### Technical Service:

(877) 477-8327 and (310) 898-3304

### SCIGRIP Americas

#### Sales & Marketing

600 Ellis Road  
Durham, NC 27703

Tel: (919) 598-2400

Fax: (919) 598-2439

Email: info@scigrip-americas.com

